

airfel



LNTY-G SERIES

High Wall (Fixed Speed Compressor) - Heat Pump



WiFi Control

Convenient remote operation through an easily navigated mobile app to adjust temperature and other comfort enabling settings.



I-Set Mode

The unit can go into the memory mode to automatically run the saved setting with the press of a single button.



Turbo Cooling

Boosting cooling and heating to quickly reach the desired temperature with assisted airflow.



Golden Fin Coating

Anticorrosive golden coating to protect against harsh conditions and improve heat efficiency.



Intelligent Airflow

Directing the cold air towards the ceiling and hot air towards the floor to avoid cold drafts blowing on the user.



3D Airflow

The vertical and horizontal louvers swing at wide angles to prevent blind spots and provide wider and more even cooling.

R410A
REFRIGERANT

Spec Table - Heat & Cool



18 & 24K



30 & 36K

AIRFEL MODEL NO	IDU		LNTYGQ18VLK	LNTYGQ24VLK	LNTYGQ30VLK	LNTYGQ36VLK
	ODU		MNYGQ18VLKW	MNYGQ24VLKW	MNYGQ30VLKW	MNYGQ36VLKW
Type			Wall Type, Non Inverter Heat Pump Split Air-Conditioner			
Power supply			230V~1 Phase, 60Hz			
Cooling T1	Rated capacity	Btu/h	18200	22500	26400	28800
	power input	W	1517	1899	2173	2323
	EER	Btu/h/W;	12.00	11.85	12.15	12.40
Cooling T3	Rated capacity	Btu/h	16400	19300	23400	24800
	power input	W	1871	2311	2690	2851
	EER	Btu/h/W;	8.75	8.35	8.70	8.70
Heating	Rated capacity	W	5000	6900	7400	8000
	power input	W	1408	2029	2056	2222
	COP	W/W	3.55	3.40	3.60	3.60
SEER		Btu/(W.h)	10.30	10.05	10.35	10.45
SEER Energy class			D	D	D	D
Indoor Unit	Rated Air flow (Hi)	m3/h	1200	1300	1500	1500
	Sound Pressure level (Hi)	dB(A)	47	50	52	51
	Dimension (WxHx D)	mm	1100×333×222	1100×333×222	1191×360×258	1191*360*258
	Packing (WxHx D)	mm	1165×405×295	1165×405×295	1260×430×328	1260×430×328
	Net/Gross weight	Kg	14 / 16	15 / 18	18 / 22	18 / 22
Outdoor Unit	Sound Pressure level (Hi)	dB(A)	54	58	60	55
	Dimension (WxDx H)	mm	920x380x699	978×421×803	978×421×803	978×421×803
	Packing (WxDx H)	mm	950x420x732	1022x480x835	1022x480x835	1022x480x835
	Net/Gross weight	Kg	44 / 49	54 / 58	52 / 60	63 / 72
Compressor	Type		Rotary	Rotary	Rotary	Rotary
Controller			Infra red Wireless Remote Controller			
Refrigerant Type / Weight		kg	R410A /1.23 kg	R410A /1.690 kg	R410A / 2.050 kg	R410A /2.300 kg
Refrigerant piping	Size - Gas Pipe	mm (Inches)	Φ12 (1/2")	Φ12 (1/2")	Φ15.88 (5/8")	Φ15.88 (5/8")
	Size - Liquid Pipe	mm (Inches)	Φ6 (1/4")	Φ6 (1/4")	Φ6 (1/4")	Φ6 (1/4")
	Max. pipe length	m	25	25	25	25
	Max. difference in level	m	20	20	20	20

Riyadh Head Office

Address : King Abdul Aziz Road,
Al Sahafa Area, Sheeha
center, 1st Floor.
Tel : +966 11 510 8500
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Jeddah Branch

Address : Prince Saud Al Faisal St,
Al Rawdah District,
Taher Tower, 6th Floor.
Tel : +966 12 511 6360
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Dammam Branch

Address : Prince Mohammed Bin
Fahad St, Al Shate'a
Business Center, 4th Floor.
Tel : +966 13 808 1312
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Tabuk Branch

Address : King Fahad Main Road,
Sultana District,
Ground Floor.
Toll free : +966 800 111 0909
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com



Download Wi-Fi Application
SmartLife-SmartHome



Android



iOS



Daikin Saudi
Call Center
800 111 0909
الرقم المجاني
Toll Free

