

airfel



LNTZ-G SERIES

High Wall (Fixed Speed Compressor) – Cool Only



WiFi Control

Convenient remote operation through an easily navigated mobile app to adjust temperature and other comfort enabling settings.



I-Set Mode

The unit can go into the memory mode to automatically run the saved setting with the press of a single button.



Turbo Cooling

Boosting cooling and heating to quickly reach the desired temperature with assisted airflow.



Golden Fin Coating

Anticorrosive golden coating to protect against harsh conditions and improve heat efficiency.



Intelligent Airflow

Directing the cold air towards the ceiling and hot air towards the floor to avoid cold drafts blowing on the user.



3D Airflow

The vertical and horizontal louvers swing at wide angles to prevent blind spots and provide wider and more even cooling.

R410A
REFRIGERANT

Spec Table - Cool Only



18 & 24K



30 & 36K

AIRFEL MODEL NO	IDU		LNTZGQ18VLK	LNTZGQ24VLK	LNTZGQ30VLK	LNTZGQ36VLK
	ODU		MNZGQ18VLKW	MNZGQ24VLKW	MNZGQ30VLKW	MNZGQ36VLKW
Type			Wall Type, Non Inverter Cooling Only Split Air-Conditioner			
Power supply			230V~1 Phase, 60Hz			
Cooling T1	Rated capacity	Btu/h	18500	22800	27200	28600
	power input	W	1516	1924	2194	2383
	EER	Btu/h/W;	12.20	11.85	12.40	12.00
Cooling T3	Rated capacity	Btu/h	16100	19600	23600	24600
	power input	W	1894	2333	2713	2764
	EER	Btu/h/W;	8.50	8.40	8.70	8.90
Heating	Rated capacity	W	NA	NA	NA	NA
	power input	W				
	COP	W/W				
SEER		Btu/(W.h)	10.30	10.05	10.45	10.30
SEER Energy class			D	D	D	D
Indoor Unit	Rated Air flow (Hi)	m3/h	1200	1300	1500	1500
	Sound Pressure level	dB(A)	47	50	52	52
	Dimension (WxHx D)	mm	1100×333×222	1100×333×222	1191×360×258	1191×360×258
	Packing (WxHx D)	mm	1165×405×295	1165×405×295	1260×430×328	1260×430×328
	Net/Gross weight	Kg	14 / 16	15 / 18	18 / 22	18 / 22
Outdoor Unit	Sound Pressure level	dB(A)	54	58	60	59
	Dimension (WxDx H)	mm	853×349×602	978×421×803	978×421×803	978×421×803
	Packing (WxDx H)	mm	890×385×628	1022x480x835	1022x480x835	1022x480x835
	Net/Gross weight	Kg	34 / 38	50 / 56	51 / 59	54 / 63
Compressor	Type		Rotary	Rotary	Rotary	Rotary
Controller			Infra red Wireless Remote Controller			
Refrigerant Type / Weight		kg	R410A /0.810kg	R410A /1.25 kg	R410A/ 1.440 kg	R410A/ 1.630 kg
Refrigerant piping	Size - Gas Pipe	mm (Inches)	Φ12(1/2")	Φ12(1/2")	Φ15.88(5/8")	Φ15.88(5/8")
	Size - Liquid Pipe	mm (Inches)	Φ6(1/4")	Φ6(1/4")	Φ6(1/4")	Φ6(1/4")
	Max. pipe length	m	25	25	25	25
	Max. difference in level	m	20	20	20	20

Riyadh Head Office

Address : King Abdul Aziz Road,
Al Sahafa Area, Sheeha
center, 1st Floor.
Tel : +966 11 510 8500
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Jeddah Branch

Address : Prince Saud Al Faisal St,
Al Rawdah District,
Taher Tower, 6th Floor.
Tel : +966 12 511 6360
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Dammam Branch

Address : Prince Mohammed Bin
Fahad St, Al Shatea
Business Center, 4th Floor.
Tel : +966 13 808 1312
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Tabuk Branch

Address : King Fahad Main Road,
Sultana District,
Ground Floor.
Toll free : +966 800 111 0909
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com



Download Wi-Fi Application
SmartLife-SmartHome



Android



iOS



Daikin Saudi
Call Center
800 111 0909
الرقم المجاني
Toll Free

