

airfel



LXTZ-G SERIES

High Wall Inverter - Cool Only



WiFi Control

Convenient remote operation through an easily navigated mobile app to adjust temperature and other comfort enabling settings.



I-Set Mode

The unit can go into the memory mode to automatically run the saved setting with the press of a single button.



Turbo Cooling

Boosting cooling and heating to quickly reach the desired temperature with assisted airflow.



Golden Fin Coating

Anticorrosive golden coating to protect against harsh conditions and improve heat efficiency.



Intelligent Airflow

Directing the cold air towards the ceiling and hot air towards the floor to avoid cold drafts blowing on the user.



3D Airflow

The vertical and horizontal louvers swing at wide angles to prevent blind spots and provide wider and more even cooling.

INVERTER

R410A
REFRIGERANT

Spec Table - Inverter Cool Only



AIRFEL MODEL NO		IDU	LXTZGQ12VLK	LXTZGQ18VLK	LXTZGQ24VLK
		ODU	MXYGQ12VLK	MXYGQ18VLK	MXYGQ24VLK
Type			Wall Type Inverter Cooling Only Split Air-Conditioner		
Power supply			230V~1 Phase, 60Hz		
Cooling T1	Rated capacity	Btu/h	12100	18400	23000
	power input	W	1008	1508	1885
	EER	Btu/h/W;	12.00	12.20	12.20
Cooling T3	Rated capacity	Btu/h	11100	16900	21600
	power input	W	1261	1878	2483
	EER	Btu/h/W;	8.80	9.00	8.70
Heating	Rated capacity	W	NA	NA	NA
	power input	W			
	COP	W/W			
SEER		Btu/(W.h)	15	15.15	13.50
SEER Energy class			B	B	C
Indoor Unit	Rated Air flow (Hi)	m3/h	700	970	970
	Size - Gas Pipe	dB(A)	41	48	48
	Size - Liquid Pipe	mm	920×306×195	1100×333×222	1100×333×222
	Packing (WxHx D)	mm	990×380×265	1165×405×295	1165×405×295
	Net/Gross weight	Kg	10 / 12	14 / 17	15 / 18
Outdoor Unit	Sound Pressure level	dB(A)	54	57	58
	Dimension(WxDxH)	mm	795×305×550	853×349×602	920×380×699
	Packing (WxDx H)	mm	835×340×585	890×385×628	960×430×732
	Net/Gross weight	Kg	22 / 26	29 / 32	36 / 41
Compressor	Type		Inverter Rotary		
Controller	Type		Infra red Wireless Remote Controller		
Refrigerant Type / Weight		kg	R410A/0.65	R410A/0.9	R410A/0.96
Refrigerant piping	Size - Gas Pipe	mm (Inches)	Φ9.52 (3/8")	Φ12 (1/2")	Φ15.88 (5/8")
	Size - Liquid Pipe	mm (Inches)	Φ6 (1/4")	Φ6 (1/4")	Φ6 (1/4")
	Max. pipe length	m	25	25	25
	Max. difference in level	m	20	20	20

Riyadh Head Office

Address : King Abdul Aziz Road,
Al Sahafa Area, Sheeha
center, 1st Floor.
Tel : +966 11 510 8500
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Jeddah Branch

Address : Prince Saud Al Faisal St,
Al Rawdah District,
Taher Tower, 6th Floor.
Tel : +966 12 511 6360
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Dammam Branch

Address : Prince Mohammed Bin
Fahad St, Al Shate'a
Business Center, 4th Floor.
Tel : +966 13 808 1312
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com

Tabuk Branch

Address : King Fahad Main Road,
Sultana District,
Ground Floor.
Toll free : +966 800 111 0909
E-mail : info@daikin-ksa.com
Website : www.daikin-ksa.com



Download Wi-Fi Application
SmartLife-SmarHome



Android



iOS



Daikin Saudi
Call Center
800 111 0909
الرقم المجاني
Toll Free

